



Customer Fulfillment Responsibilities for OFE Trailers

Due to the trailers being OFE'd (Owner Furnished Equipment) you will need to take responsibility for the following:

NOTE: this is list assembled based upon the requirements for a Blueprint Solution but should be the minimum for any size trailer being provided.

- (1-6) Blueprint cases a 6x12 Trailer is recommended, 7-8 Blueprint cases a 7x16 Trailer is recommended
- Rear door height of no less than 70"
- External wheel wells
- No side door -> There is a side door then a step shim would need to be built
- Transition plates (2) -> Door flap to ground level and body of trailer to door flap
- Preferably insulated -> Reduces potential for condensation buildup in trailer
- The narrowest internal width of no less than 60"
- (1) Hitch - Rated for 7,500 lbs. Load Distribution and Sway systems included.
- (1) Hitch Ball, 2-5/16" x 1-1/4" x 2-1/4", 12,000 GTW Zinc
- (4) Rubber Wheel Chock (8" x 6" x 5")
- (1) Coupler Lock Master #379 for 2 5/16 Hitch
- (2) No. 5 Master Padlock
- Tie down solution (PCI recommends an E-Track system)
 - (one on each side) E-Track that spans from nose of trailer to back of the trailer with the bottom of the e-track being 30" from the floor spanning 4" tall
 - (2) E-Track Beam Socket (pair)
 - (2) 12' x 2" E-Track Tiedowns (Yellow)

Due to this being an OFE trailer, any issues that may arise causing fixes and other repairs to be made so that the cases can fit will be the responsibility and cost of the client to cover.